

Annex A

Complete specification of IV Catheter G 24 and G26

Catheter hub: Teflon fluoro ethyl propylene (FEP); Catheter (Distal Part): transparent, straight, with 2-4 full embed X-ray contrast lines and tapered end; The X-ray line allows better control over the catheter and the internal needle when doing a vein puncture under poor lighting conditions. Injection port with bacterial filter and removable reusable cap or cone (for closing) attached with fixed strap. The cap should be free of protuberances. Fixation wing: sloped supporting surface to compensate for puncture gradient. Luer connection (proximal part): for attachment of an infusion syringe with Luer-Lock fitting. Internal needle or trocar with bevelled edge for good skin penetration and reduced vein trauma. The internal needle is connected to a transparent flashback chamber with handgrip and stopper. The transparent base enables monitoring for blood reflux when a vein is punctured. Color-coded hub and cannula, by size:

24G 0.7x19 mm, yellow: average flow 18 ml/mm, neonatal use

26G 0.6x19 mm, purple: average flow 13 ml/mm, neonatal use

Complete specification of Nelaton Catheter Fr 8-18

Non toxic, non irritant medical grade PVC compatible with catheter lubricants. Frozen suture tubing for super smooth intubation. Distal end is coned for non traumatic introduction with 2 lateral eyes for efficient drainage. Proximal end is fitted with universal funnel shaped connector for extension. Funnel Shape connectors are color coded for instant identification of sizes.

Blue 8Fr/ Ch 400mm

Black 10Fr/ Ch 400mm

White 12Fr/ Ch 400mm

Green 14Fr/ Ch 400mm

Orange 16Fr/ Ch 400mm

Red 18Fr/ Ch 400mm

Complete specification of Suction Catheter Fr 5-18

Open distal end with elliptical eye for easy and efficient suction

Provided with X-ray opaque line radiological identification

Available with thumb control device for positive control during suction

Smooth Chair PVC

Color-coded connector at proximal end for instant identification

Gray 5 Fr / 2.0 mm

Blue 8 Fr / 2.7mm

Black 10 Fr / 3.0mm

White 12 Fr / 4.0mm

Green 14 Fr / 4.7mm

Orange 16Fr / 5.3mm

Red 18Fr / 6.0mm